

Open-spec RK3328 SBC offers dual GbE for \$22

By *Rianne Schestowitz*

Created 25/03/2020 - 4:30pm

Submitted by Rianne Schestowitz on Wednesday 25th of March 2020 04:30:35 PM Filed under [Linux](#) [1] [Ubuntu](#) [2]



FriendlyElec's \$22 NanoPi R2S router SBC runs FriendlyWrt or Ubuntu Core on a quad-A53 RK3328 with 1GB DDR4, a pair each of USB and 941Mbps Gigabit Ethernet ports, and an optional \$3 case.

FriendlyElec has launched an update to its community-backed NanoPi R1S-H3, NanoPi R1S-H5, and earlier NanoPi R1 router boards that similarly targets basic routing and IoT duties. The NanoPi R2S switches from the quad-core Cortex-A7 Allwinner H3 on the R1S-H3 and the quad-A53 Allwinner H5 on the R1S-H5 to tap the quad-A53 Rockchip RK3328. The SoC is clocked here at 1.4GHz compared to 1.2GHz on the NanoPi R1S-H5's Allwinner H5.

[3]

[Linux Ubuntu](#)

Source URL: <http://www.tuxmachines.org/node/135608>

Links:

[1] <http://www.tuxmachines.org/taxonomy/term/63>

[2] <http://www.tuxmachines.org/taxonomy/term/121>

[3] <http://linuxgizmos.com/open-spec-rk3328-sbc-offers-dual-gbe-for-22/>